



MATERIAL SAFETY DATA SHEET

(In accordance with ISO 11014-1 Standard)

Product Name: Tissue-Tek® Paraform® Processing/Embedding Medium, Formula 3

Revision Date: 2008-12-01

1. Identification of the Substance

Product Name: Tissue-Tek® Paraform® Processing/Embedding Medium, Formula 3– (Product Code #7052)

Synonym(s): N/A

General Use: Tissue-Tek® AutoTEC® Embedding System and Manual Embedding Systems

Manufactured For: Sakura Finetek USA, Inc.
Torrance, CA 90501 U.S.A.
Tel: 310-972-7800

Emergency Telephone Number:
800-424-9300 (Chemtrec)

2. Composition/Data on Components

Component Name	CAS#	Concentration	OSHA (PEL)	ACGIH (TLV)	R Phrases	Classification
Paraffin	8002-74-2	Trade Secret	Fume 2 mg/m3	Fume 2 mg/m3	R-None	None

3. Hazards Identification

Main Hazards: Not classified as hazardous.

Routes of Entry: Eye contact, skin contact

Carcinogenic Status: Not considered carcinogenic by NTP, IARC, and OSHA

Health Effects

Eyes: Contact may cause slight transient irritation.

Skin: Material may cause irritation.

Ingestion: No adverse effects are expected.

Inhalation: No adverse effects are expected during normal conditions of use. Inhalation of paraffin wax fumes during heating may irritate the eyes, nose, and throat.

HMIS Rating

Health: 1
Flammability: 1
Reactivity: 0
Protection: C

HMIS Rating Scale

Minimal: 0
Slight: 1
Moderate: 2
High: 3
Severe: 4

HMIS Rating Notes:

Protection = C (Safety glasses, gloves, apron)

4. First Aid Measures

Inhalation: If there is difficulty in breathing, give oxygen. Seek medical attention if symptoms persist.

Ingestion: Do not induce vomiting. Have victim drink 1-3 glasses of water to dilute stomach contents. Never administer anything by mouth if a victim is losing consciousness, is unconscious, or is convulsing. Obtain medical attention immediately.

Skin: If skin irritation develops, or other symptoms occur, discontinue use. Wash with Soap and large amounts of water for at least 15 minutes. Seek medical attention if symptoms persist. Contaminated clothing should be washed or dry cleaned before re-use.

Eye: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Advice to Physicians: Treat symptomatically.

5. Fire Fighting Measures

Unusual Fire and Explosion Hazards: This product may give rise to hazardous fumes in a fire.

Extinguishing Media: Dry Chemical, Carbon Dioxide, Water Spray, Alcohol Foam.

Protective Equipment for Fire Fighting: Wear NIOSH/MSHA approved self-contained breathing apparatus and protective clothing.

MATERIAL SAFETY DATA SHEET

Product Name: Tissue-Tek[®] Paraform[®] Processing/Embedding Medium, Formula 3

Revision Date: 2008-12-01

6. Accidental Release Measures

This product may be collected by carefully scooping into a pan, paper towel, or other absorbent material. If wax is hot, let cool before initiating cleanup. To clean up spills of cooled wax, use non-sparking tools to scrape the wax into suitable containers for disposal. Wear appropriate protective clothing.

7. Handling and Storage

Keep containers closed when not in use. Storage area should be cool, dry, and well ventilated. Keep away from incompatible materials.

8. Exposure Controls/Personal Protection

Occupational Exposure Standards

Paraffin: (fume)ACGIH TLV 2 mg/m³ 8Hr TWA

Engineering Control Measures: No specific measures necessary. Good general room ventilation is expected to be adequate to control airborne levels. Heating of this product may generate vapors or fumes, therefore, local exhaust ventilation is recommended to keep airborne concentrations below exposure limits.

Respiratory Protection: Self contained breathing apparatus.

Hand Protection: Chemical resistant gloves.

Eye Protection: Chemical goggles or safety glasses with side shields.

Body Protection: Apron.

9. Physical and Chemical Properties

Physical State: Wax prill

Color: Colorless to white

Odor: Odorless

pH: No data available.

Boiling Point: No data available.

Melting Point: 132-136°F (56-58°C)

Flash Point: 410°F (210°C)

Auto-Ignition Temp: 473°F (245°C)

Explosion Limits (%): No data available.

Specific Gravity: 0.8.

Vapor Pressure: No data available.

Volatile By Volume: N/A

Evaporation Rate (n-Butyl Acetate = 1): N/A

Solubility in water: Insoluble

Reactivity in Water: No

Vapor Density (Air=1) : No data available.

Viscosity (cSt): No data available.

10. Stability and Reactivity

Stability: Stable under normal conditions.

Conditions to Avoid: Heat and open flame.

Materials To Avoid: Reducing agents and acids.

Hazardous Decomposition Products: May emit toxic fumes.

Hazardous Polymerization: N/A.

11. Toxicological Information

Acute Toxicity: Low order of acute toxicity predicted

Paraffin: A 100 mg dose applied to the rabbit eye for 24 hours caused mild irritation. A 500 mg dose applied to the rabbit skin for 24 hours caused mild irritation.

Chronic Toxicity/Carcinogenicity: Paraffin: When implanted in rats (120 mg/kg) and mice (480-660 mg/kg) caused tumors of the bladder, lungs, and thorax.

Genotoxicity: This product is not expected to cause any mutagenic effects.

Reproductive/Developmental Toxicity: This product is not expected to cause reproductive or developmental health effects.

MATERIAL SAFETY DATA SHEET

Product Name: Tissue-Tek® Paraform® Processing/Embedding Medium, Formula 3

Revision Date: 2008-12-01

12. Ecological Information

Mobility: No relevant studies identified.

Persistence/Degradability: No relevant studies identified.

Bio-accumulation: No relevant studies identified.

Ecotoxicity: No relevant studies identified.

13. Advice on Disposal

Dispose of in accordance with all applicable Federal, State, and Local regulations (see section 15).

14. Transport Information

DOT CFR 172.101 Data: Not regulated.

UN Proper Shipping Name: Not regulated.

UN Class: None.

UN Number: None.

UN Packaging Group: None.

15. Regulatory Information

Labeling Information

Health: Not Classified

Safety: Not Classified

Environment: Not Classified

EC Annex/Classification: According to EC Commission Directive 67/548/EEC this product is not classified.

R phrases: None

S phrases: None

TSCA Listing: All ingredients have been verified for inclusion on the EPA Toxic Substance Control Act Chemical Substance Inventory.

EINECS Listing: All ingredients in this product are listed on the European Inventory of Existing Commercial Chemical Substances (EINECS) or the European List of New Chemical Substances (ELINCS) or are exempt from listing.

DSL/NDSL (Canadian) Listing: All ingredients in this product are listed on the Domestic Substance List (DSL) or the Non-Domestic Substance List (NDSL).

MA Right to Know Law: All components have been checked for inclusion on the Massachusetts Substance List (MSL). Those components present at or above the minimum concentration include: Paraffin, Butylated Hydroxytoluene.

PA Right to Know Law: This product contains the following chemical found on the Pennsylvania Hazardous Substance List: Paraffin, Butylated Hydroxytoluene.

NJ Right to Know Law: This product does not contain any chemicals on the New Jersey Workplace Hazardous Substance List: Butylated Hydroxytoluene

CA Proposition 65: This product does not contain materials which the state of California has found to cause cancer, birth defects or other reproductive harm.

SARA Title III Sect. 302 (EHS): This product does not contain any chemical subject to SARA Title III Section 302.

SARA Title III Sect. 304: This product does not contain any chemicals subject to SARA Title III Section 304.

SARA Title III Sect. 311/312 Categorization: Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

SARA Title III Sect. 313: This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

16. Other Information

NFPA Ratings:

NFPA Code for Flammability – 1

NFPA Code for Health – 1

NFPA Code for Reactivity – 0

NFPA Code for Special Hazards – None

This Material Safety Data Sheet has been furnished on request. A revised Material Safety Data Sheet will be furnished only if requested, also in case of specification changes. The above information, which is accurate to the best of our knowledge and belief, describes the safety aspects of our product but does not warrant any product properties. The company gives no warranty as to the accuracy or completeness of such information. It is the user's responsibility to determine the suitability of the information for their particular purposes.

0002293-02 Rev B